

MODEL SERIES WFQT27300

QuickTwist™ 2 Stage Drinking Water Filtration System

Replacement Cartridges: **WFQTC70001, WFQTC3001 Series**



Tested and Certified by Water Quality Association (WQA) against NSF/ANSI Standard 42 for Aesthetic Chlorine Reduction, Taste and Odor Reduction, and Particulate Reduction - Class 1 (0.5 µm to < 1 µm), as verified and substantiated by test data. Certified by Water Quality Association (WQA) against NSF/ANSI Standard 53 for the reduction of the contaminants specified on our Performance Data Sheet, as verified and substantiated by test data. Certified for Cyst Reduction. Chemical and mechanical reduction unit.

For conditions of use and replacement parts, please see our Performance Data Sheet. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after this filter system. Maximum operating temperature 38° C/100° F. Systems certified for cysts reduction may be used on disinfected waters that may contain **filterable cysts**. Operating pressure 30-100 psi/207-690 kPa.

866-709-2086 Service Requests/Product Information
800-441-7515 Safety/Health Questions
Protect Plus, LLC Hickory, NC 28601 USA
www.waterfiltration.DuPont.com

V4.0

File Ref: WFQT27300 - Data Plate

P